

SAFETY DATA SHEET

SHELL UNLEADED PETROL 95

Infosafe No.: LQ4CH
ISSUED Date : 22/09/2022
ISSUED by: VIVA ENERGY AUSTRALIA PTY LTD
(FORMERLY: SHELL COMPANY OF AUSTRALIA LTD)

Section 1 - Identification

Product Identifier

SHELL UNLEADED PETROL 95

Company Name

VIVA ENERGY AUSTRALIA PTY LTD (FORMERLY: SHELL COMPANY OF AUSTRALIA LTD) (ABN 46 004 610 459)

Address

Level 16, 720 Bourke Street Docklands
VIC 3008 AUSTRALIA

Telephone/Fax Number

Tel: +61 (0)3 8823 4444
Fax: +61 (0)3 8823 4800

Emergency Phone Number

1800 651 818 (Australia) / Poisons Information Centre:13 11 26 (Australia)

Recommended use of the chemical and restrictions on use

Fuel for spark ignition engines designed to run on unleaded fuel. This product is intended for use in closed systems only.

Other Names

| Name |
|------------------------------------|
| SHELL LOW AROMATIC UNLEADED PETROL |
| UNLEADED 98 |
| SHELL UNLEADED PETROL 98 |
| SHELL PREMIUM UNLEADED 98 |
| SHELL UNLEADED PETROL 91 |
| UNLEADED PETROL 91 |
| UNLEADED PETROL 95 |
| PREMIUM UNLEADED PETROL |
| SHELL V POWER |

Illicit Drug Precursors

This product contains a Category III: Illicit Drug Reagent/Essential Chemical in the Code of Practice for Supply Diversion into Illicit Drug Manufacture.

Section 2 - Hazard(s) Identification

GHS classification of the substance/mixture

Classified as Hazardous according to the Globally Harmonised System of Classification and labelling of Chemicals (GHS) including Work, Health and Safety regulations, Australia.

Classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Flammable liquids: Category 1

Skin corrosion/irritation: Category 2

Eye damage/irritation: Category 2A
Germ cell mutagenicity: Category 1B
Carcinogenicity: Category 1A
Reproductive toxicity: Category 1A
Specific target organ toxicity (single exposure): Category 3 (Narcotic)
Specific target organ toxicity (repeated exposure): Category 1
Aspiration hazard: Category 1
Hazardous to the Aquatic Environment - Acute Hazard: Category 2
Hazardous to the Aquatic Environment - Long-Term Hazard: Category 2

Signal Word (s)

DANGER

Hazard Statement (s)

H224 Extremely flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H340 May cause genetic defects.
H350 May cause cancer.
H360 May damage fertility or the unborn child.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H304 May be fatal if swallowed and enters airways.
H411 Toxic to aquatic life with long lasting effects.

Pictogram (s)

Flame, Exclamation mark, Health hazard, Environment

**Precautionary Statement – Prevention**

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

Precautionary Statement – Response

P312 Call a POISON CENTER/doctor if you feel unwell.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor
P331 Do NOT induce vomiting.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P332+P313 If skin irritation occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists: Get medical advice/attention.
P370+P378 In case of fire: Use foam, water spray or fog to extinguish.
P391 Collect spillage.

Precautionary Statement – Storage

P403+P235 Store in a well-ventilated place. Keep cool.

P404 Store in a closed container.
P405 Store locked up.

Precautionary Statement – Disposal
P501 Dispose of contents/container to an approved waste disposal plant.

Other Information
This product contains an Ototoxic substance.
Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Section 3 - Composition and Information on Ingredients

| Ingredients | | |
|-------------------------------------|--------------|------------|
| Name | CAS | Proportion |
| Gasoline, low boiling point naphtha | 86290- 81- 5 | 90- 100 % |
| Xylene | 1330- 20- 7 | 10- <15 % |
| Toluene | 108- 88- 3 | 10- <15 % |
| Ethylbenzene | 100- 41- 4 | 5- <10 % |
| cyclohexane | 110- 82- 7 | 2- 5 % |
| n- hexane | 110- 54- 3 | 1- 5 % |
| Trimethyl Benzene | 25551- 13- 7 | <2. 5 % |
| BENZENE | 71- 43- 2 | <= 1 % |

Preparation Description
Complex mixture of hydrocarbons consisting of paraffins, cycloparaffins, aromatic and olefinic hydrocarbons (including benzene at 1.0%v/v maximum), with carbon numbers predominantly in the C4 to C12 range. May also contain several additives at <0.1% v/v each.

Other Information
Contains Benzene, CAS # 71-43-2. Contains Toluene, CAS # 108-88-3. Contains Ethylbenzene, CAS # 100-41-4. Contains n-Hexane, CAS # 110-54-3. Contains Xylene (Mixed Isomers), CAS # 1330-20-7. Contains Naphthalene, CAS # 91-20-3. Contains Cyclo-hexane, CAS# 110-82-7. Contains Tri-methyl-benzene (all isomers), CAS# 25551-13-7. Dyes and markers can be used to indicate tax status and prevent fraud.

Section 4 - First Aid Measures

Inhalation
If inhaled, remove affected person from contaminated area. Apply artificial respiration if not breathing. Seek medical attention.

Ingestion
Do NOT induce vomiting. Wash out mouth and lips with water. Where vomiting occurs naturally have affected person place head below hip level in order to reduce risk of aspiration. Seek immediate medical attention.

Skin
Remove all contaminated clothing immediately. Wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse or discard. Seek medical attention.

Eye
If in eyes, hold eyelids apart and flush the eyes continuously with running water. Remove contact lenses. Continue flushing for several minutes until all contaminants are washed out completely. Seek medical attention.

First Aid Facilities
Eyewash, safety shower and normal washroom facilities.

Advice to Doctor
Treat symptomatically.

Other Information
For advice in an emergency, contact a Poisons Information Centre (Phone Australia 131 126) or a doctor at once.

Section 5 - Firefighting Measures

Suitable Extinguishing Media

Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable Extinguishing Media

Do not use water jet.

Hazards from Combustion Products

Under fire conditions this product may emit toxic and/or irritating fumes, smoke and gases including carbon monoxide, carbon dioxide and oxides of nitrogen.

Specific hazards arising from the chemical

Extremely flammable liquid and vapour. Keep containers and fire-exposed surfaces cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition. Vapour/air mixtures may ignite explosively. Flashback along the vapour trail may occur. Runoff to sewer may create fire or explosion hazard.

Hazchem Code

3YE

Decomposition Temperature

Not available

Precautions in connection with Fire

Fire fighters should wear full protective clothing and self-contained breathing apparatus (SCBA) operated in positive pressure mode. In case of fire the product may be violently or explosively reactive. Use water spray to disperse vapours. This product should be prevented from entering drains and watercourses.

Section 6 - Accidental Release Measures

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water and waste management authorities in accordance with local regulations.

Section 7 - Handling and Storage

Precautions for Safe Handling

Wear appropriate personal protective equipment and clothing to prevent exposure. Handle and use the material in a well-ventilated area, away from sparks, flames and other ignition sources. Have emergency equipment (for fires, spills, leaks, etc.) readily available. Work from suitable, labelled, fire-resistant containers. Open containers carefully as they may be under pressure. Keep containers tightly closed. Flameproof equipment is necessary in areas where the product is being used. Take precautionary measures against static discharges. Earth or bond all equipment. Do not empty into drains. Ensure a high level of personal hygiene is maintained when using this product, that is, always wash hands before eating, drinking, smoking or using the toilet facilities.

Avoid exposure. Do not handle until all safety precautions have been read and understood. It is recommended that pregnant or breastfeeding women should not handle this product unless adequate exposure protection can be assured at all times. Female personnel planning pregnancy should be made aware of the potential risks.

Conditions for safe storage, including any incompatibilities

Store in a well ventilated area away from heat and sources of ignition, out of direct sunlight and moisture. Take precautions against static electricity discharges. Use proper grounding procedures. Store away from incompatible materials such as materials that support combustion (oxidising materials). Store in suitable, labelled containers. Inspect periodically for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Ensure that storage conditions comply with applicable local and national regulations.

For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids.

Unsuitable Materials

Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are: natural rubber (NR), nitrile rubber (NBR), ethylene propylene rubber (EPDM), polymethyl methacrylate (PMMA), polystyrene, polyvinyl chloride (PVC), polyisobutylene.; However, some may be suitable for glove materials.

Section 8 - Exposure Controls and Personal Protection

Occupational exposure limit values

No exposure standards have been established for this material. However, the available exposure limits for ingredients are listed below:

Benzene

TWA: 1 ppm, 3.2 mg/m³

Note: Carc.1A

Xylene

TWA: 80 ppm, 350 mg/m³

STEL: 150 ppm, 655 mg/m³

Toluene

TWA: 50 ppm, 191 mg/m³

STEL: 150 ppm, 574 mg/m³

Note: Sk

Ethylbenzene

TWA: 100 ppm, 434 mg/m³

STEL: 125 ppm, 543 mg/m³

Gasoline

TWA: 900 mg/m³

Cyclohexane

TWA: 100 ppm, 350 mg/m³

STEL: 300 ppm, 1050 mg/m³

n-hexane

TWA: 20 ppm, 72 mg/m³

Trimethylbenzenes

TWA: 25 ppm, 123 mg/m³

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

'Sk' Notice: Absorption through the skin may be a significant source of exposure. The exposure standard is invalidated if such contact should occur.

Source: Safe Work Australia

Biological Monitoring

Name: n-hexane

Determinant: 2,5-Hexanedione in urine**

Value: 0.5 mg/l

Sampling time: End of shift.

**without hydrolysis

Name: Benzene

Determinant: S-Phenylmercapturic acid in urine

Value: 25 µg/g creatinine

Sampling time: End of shift.

Determinant: t,t-Muconic acid in urine

Value: 500 µg/g creatinine

Sampling time: End of shift.

Name: Xylenes

Determinant: Methylhippuric acids

Specimen: Creatinine in urine.

Value: 1.5g/g

Sampling time: End of shift.

Name: Ethylbenzene

Determinant: Sum of mandelic acid and phenylglyoxylic acid.

Specimen: Creatinine in urine.

Value: 0.15 g/g

Sampling time: End of shift.

Name: Toluene

Determinant: Toluene in blood

Value: 0.02 mg/L
Sampling time: Prior to last shift of workweek
Determinant: Toluene in urine
Value: 0.03 mg/L
Sampling time: End of shift.
Determinant: o-Cresol in urine*
Value: 0.3 mg/g creatinine
Sampling time: End of shift.
* with hydrolysis
Source: American Conference of Industrial Hygienists (ACGIH)

Control Banding
Not available

Engineering Controls
This substance is hazardous and should be used with a local exhaust ventilation system, drawing vapours away from workers' breathing zone. A flame-proof exhaust ventilation system is required. If the engineering controls are not sufficient to maintain concentrations of vapours/mists below the exposure standards, suitable respiratory protection must be worn. Refer to relevant regulations for further information concerning ventilation requirements.
Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 60079.10.1 Explosive atmospheres - Classification of areas - Explosive gas atmospheres, for further information concerning ventilation requirements.

Respiratory Protection
If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable vapor/mist filter should be used. Refer to relevant regulations for further information concerning respiratory protective requirements.
Reference should be made to Australian Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye and Face Protection
Safety glasses with side shields, chemical goggles or full-face shield as appropriate should be used. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform to relevant regulations. Eye protection should conform with Australian/New Zealand Standard AS/NZS 1337 (series) - Eye Protectors for Industrial Applications.

Hand Protection
Wear gloves of impervious material nitrile gloves may be suitable. (Breakthrough time of > 240 minutes.) For incidental contact/splash protection Neoprene, PVC gloves may be suitable. Final choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Occupational protective gloves should conform to relevant regulations.
Reference should be made to AS/NZS 2161.1: Occupational protective gloves - Selection, use and maintenance.

Thermal Hazards
No further relevant information available.

Body Protection
Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled.

Section 9 - Physical and Chemical Properties

| Properties | Description | Properties | Description |
|--|---------------------------|---------------------------|-----------------------------------|
| Form | Liquid | Appearance | Red, Yellow or colourless liquid. |
| Colour | Red, Yellow or colourless | Odour | Hydrocarbon |
| Melting Point | Not available | Freezing Point | Not available |
| Boiling Point | 35 - 210 °C | Decomposition Temperature | Not available |
| Solubility in Water | Not available | Specific Gravity | 0.71 - 0.77 gm/cm³ at 15°C |
| pH | Not available | Vapour Pressure | 55 - 80 kPa at 37.8°C |
| Relative Vapour Density (Air=1) | Not available | Evaporation Rate | Not available |
| Odour Threshold | Not available | Volatile Component | Not available |
| Partition Coefficient: n-octanol/water (log value) | 2 - 6 | Density | Typical 0.73 g/cm³ at 15 °C |
| Flash Point | < -40 °C | Flammability | Flammable |
| Auto-Ignition Temperature | Not available | Flammable Limits - Lower | 1 %(V) |
| Flammable Limits - Upper | 8 %(V) | Kinematic Viscosity | 0.5 - 0.75 mm²/s at 40 °C |
| Particle Characteristics | Not available | | |

Section 10 - Stability and Reactivity

Reactivity

Reacts with incompatible materials.

Chemical Stability

Stable under normal conditions of storage and handling.

Possibility of hazardous reactions

Not available

Conditions to Avoid

Avoid heat, sparks, open flames and other ignition sources.

Incompatible Materials

Strong oxidising agents.

Hazardous Decomposition Products

Hazardous decomposition products are not expected to form during normal storage. Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or thermal or oxidative degradation.

Hazardous Polymerization

Not available

Section 11 - Toxicological Information

Toxicology Information

The available toxicity data for material given below.

Acute Toxicity - Oral

LD50:(Rat): >2000 mg/kg

Acute Toxicity - Dermal

LD50:(Rat): >2000 mg/kg

Acute Toxicity - Inhalation

LC50:(Rat): >5 mg/l / 4.00 h

Ingestion

May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the respiratory system during ingestion or from vomiting may cause severe pulmonary injury that may lead to death. May cause irritation to the mouth, throat, esophagus and stomach with symptoms of nausea, abdominal discomfort, vomiting and diarrhoea.

Inhalation

May cause irritation to the mucous membrane and upper airways, especially where vapours or mists are generated. Symptoms include sneezing, coughing, wheezing, shortness of breath, headache, dizziness, drowsiness, nausea and vomiting.

Skin

Causes skin irritation. Skin contact will cause redness, itching and swelling. Repeated exposure may cause skin dryness and cracking and may lead to dermatitis.

Eye

Causes serious eye irritation. On eye contact this product will cause tearing, stinging, blurred vision, and redness.

Respiratory Sensitisation

Not expected to be a respiratory sensitizer.

Skin Sensitisation

Not expected to be a skin sensitizer.

Germ Cell Mutagenicity

May cause genetic defects. Classified as Known or presumed to induce heritable mutations.

Carcinogenicity

May cause cancer. Classified as a Known or presumed human carcinogen.

Benzene is listed as a Group 1: Carcinogenic to humans according to International Agency for Research on Cancer (IARC).

Ethylbenzene and gasoline is listed as a Group 2B: Possibly carcinogenic to humans according to International Agency for Research on Cancer (IARC).

Xylene and toluene are listed as a Group 3: Not classifiable as to carcinogenicity to humans according to International Agency for Research on Cancer (IARC).

Reproductive Toxicity

05/02/2023, 19:26SDS

May damage fertility or the unborn child. Classified as a Known or presumed human reproductive or developmental toxicant.

STOT - Single Exposure
May cause drowsiness or dizziness.

STOT - Repeated Exposure
Causes damage to organs through prolonged or repeated exposure.

Aspiration Hazard
May be fatal if swallowed and enters airways.

Other Information
Repeated Dose Toxicity:
Kidney: caused kidney effects in male rats which are not considered relevant to humans
Blood-forming organs: repeated exposure affects the bone marrow. (Benzene)
Peripheral nervous system: repeated exposure causes peripheral neuropathy in animals. (n-Hexane)
Exposure to very high concentrations of similar materials has been associated with irregular heart rhythms and cardiac arrest.
Prolonged and repeated exposures to high concentrations have resulted in hearing loss in rats. Solvent abuse and noise interaction in the work environment may cause hearing loss. (Toluene)
Abuse of vapours has been associated with organ damage and death. (Toluene)
Myelodysplastic syndrome (MDS) was observed in individuals exposed to very high levels (50 ppm to 300 ppm range) of benzene over a long period of time in the workplace. The relevance of these results to lower levels of exposure is not known. (Benzene)
This product contains an Ototoxic substance. Combination with noise exposure, even at safe levels, could still cause auditory injuries and hearing loss.

Section 12 - Ecological Information

Ecotoxicity
Toxic to aquatic life with long lasting effects.

Persistence and degradability
Major constituents are expected to be inherently biodegradable. The volatile constituents will oxidize rapidly by photochemical reactions in air.

Mobility
Floats on water. Evaporates within a day from water or soil surfaces. Large volumes may penetrate soil and could contaminate groundwater. Contains volatile constituents.

Bioaccumulative Potential
Contains constituents with the potential to bioaccumulate.

Other Adverse Effects
Films formed on water may affect oxygen transfer and damage organisms.

Environmental Protection
Do not discharge this material into waterways, drains and sewers.

Acute Toxicity - Other Organisms
LL/EL/IL50:(Aquatic organisms): 1-10 mg/l

Hazardous to the Ozone Layer
This product is not expected to deplete the ozone layer.

Section 13 - Disposal Considerations

Disposal Considerations
Dispose of waste according to applicable local and national regulations. Labels should not be removed from containers until they have been cleaned. Advise flammable nature. Empty containers may contain flammable residues. Do not cut, puncture or weld on or near containers. Contaminated containers must not be treated as household waste. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Do not incinerate closed containers. Wastes including emptied containers are controlled wastes and should be disposed of in accordance with all applicable local and national regulations. Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected.
To minimise personal exposure, refer to Section 8 - Exposure Controls and Personal Protection.

Section 14 - Transport Information

Transport Information
Road and Rail Transport (ADG Code):

This material is a Class 3 - Flammable Liquid according to The Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Class 3 - Flammable Liquids are incompatible in a placard load with any of the following:

- Class 1: Explosives
- Division 2.1: Flammable Gases
- (Division 2.1 and Class 3 are incompatible in transport if both are in tanks or other receptacles with a capacity individually exceeding 500 L)
- Division 2.3: Toxic Gases
- Division 4.2: Spontaneously Combustible Substances
- Division 5.1: Oxidising substances
- Division 5.2: Organic Peroxides
- Class 6: Toxic or Infectious Substances
- (where the flammable liquid is nitromethane)
- Class 7: Radioactive materials unless specifically exempted

Marine Transport (IMO/IMDG):

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

Class/Division: 3

UN No: 1203

Proper Shipping Name: GASOLINE (MARINE POLLUTANT)

Packing Group: II

EMS : F-E, S-E

Special Provisions: 243

Air Transport (ICAO/IATA):

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air.

Class/Division: 3

UN No: 1203

Proper Shipping Name: Gasoline

Packing Group: II

Packaging Instructions (passenger & cargo): 353

Packaging Instructions (cargo only): 364

Hazard Label: Flammable Liquid

Special Provisions: A100

ADG U.N. Number

1203

ADG Proper Shipping Name

GASOLINE

ADG Transport Hazard Class

3

ADG Packing Group

II

Hazchem Code

3YE

IERG Number

14

Special Precautions for User

Not available

IMDG Marine pollutant

Yes

Transport in Bulk

Not available

Additional Information

This product is classified as Oils under MARPOL Annex I. MARPOL Annex I rules apply for bulk shipments by sea.

Section 15 - Regulatory Information

Regulatory Information

Classified as Hazardous according to the Globally Harmonised System of classification and labelling of chemicals (GHS) including Work, Health and Safety regulations, Australia.

SUSMP Schedule: Not scheduled. When packed in containers having capacity of greater than 20 litres.

SUSMP Schedule: S5. When packed in containers having capacity of less than 20 litres.

Poisons Schedule

Not Scheduled

Montreal Protocol

Not listed

Stockholm Convention

Not listed

Rotterdam Convention

Not listed

International Convention for the Prevention of Pollution from Ships (MARPOL)

This product is classified as Oils under MARPOL Annex I. MARPOL Annex I rules apply for bulk shipments by sea.

Agricultural and Veterinary Chemicals Act 1994

Not available

Basel Convention

Not available

Section 16 - Any Other Relevant Information

Date of Preparation

SDS Reviewed: September 2022

Supersedes: June 2021

Version Number

3.0

Literature References

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Standard for the Uniform Scheduling of Medicines and Poisons.

Australian Code for the Transport of Dangerous Goods by Road & Rail.

Work Health and Safety Regulations, Schedule 10: Prohibited carcinogens, restricted carcinogens and restricted hazardous chemicals.

Code of Practice for Supply Diversion into Illicit Drug Manufacture.

National Code of Practice for Chemicals of Security Concern.

Agricultural Compounds and Veterinary Chemicals Act.

International Agency for Research on Cancer (IARC) Monographs.

Montreal Protocol on Substances that Deplete the Ozone Layer.

Stockholm Convention on Persistent Organic Pollutants (POPs).

Rotterdam Convention on the Prior Informed Consent Procedure for Certain Hazardous Chemicals and Pesticides in International Trade.

Basel Convention on the Control of Transboundary Movements of Hazardous Wastes and Their Disposal.

International Air Transport Association (IATA) Dangerous Goods Regulations.

International Maritime Dangerous Goods (IMDG) Code.

Workplace exposure standards for airborne contaminants.

Adopted biological exposure determinants, American Conference of Industrial Hygienists (ACGIH).

Globally Harmonised System of Classification and Labelling of Chemicals (7th revised edition).

Code of Practice: Managing Noise and Preventing Hearing Loss at Work.

END OF SDS

© Copyright Chemical Safety International Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe SDS displayed is the intellectual property of Chemical Safety International Pty Ltd.

The compilation of SDS's displayed is the intellectual property of Chemical Safety International Pty Ltd.

Copying of any SDS displayed is permitted for personal use only and otherwise is not permitted. In particular the SDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of SDS without the express written consent of Chemical Safety International Pty Ltd.

Product Name: SHELL UNLEADED PETROL 95
Issue Date: 22/09/2022